

Dormant, semi-dormant, and non-dormant grass can all be revitalized with RegalNV Lawn Colorants. This environmentally safe and pet-friendly colorant can be used to strengthen the color of any type of turf, including golf courses, athletic fields, residential and commercial lawns, and other types of grass.

In order to obtain turf grass that appears natural and healthy, RegaINV Lawn Colorants are a conventional colorant designed to be blended or agitated with water. Carefully read all and adhere to all mixing instructions and application procedures.

MIXING INSTRUCTIONS:

Contents may settle! Shake or mix product well before use. Combine 8 ounces of RegalNV Lawn Colorants per 1 gallon of water and agitate or mix well. Mix ratio is very important for best coverage and longevity.

DO NOT ALLOW PRODUCT TO FREEZE.

COVERAGE AND APPLICATION:

Apply at a rate of 2-8 gallons of product per acre or 6-24oz per 1000ft² with the recommended amount of water making sure to follow the mixing instructions. Rates may vary depending on, but not limited to turf grass type, turf grass density, turf health. height of cut. etc.

It is recommended to cut turf grass to desired height before applying. Make sure to clear turf of any and all debris, grass clippings, leaves, etc. RegalNV Lawn Colorants are tank mix compatible with most fertilizers, herbicides, fungicides, and pesticides, however, a compatibility jar test is recommended.

Take care to prevent overspray on surfaces such as curbs, concrete, tee markers, or other objects where color is not intended. To reduce accidental overspray, promptly utilize a scrub brush soaked in a solution of soap and water.



Manufactured for Regal Chemical Co. By GreenVista Lawn Colorants Piedmont, SC 29673

EQUIPMENT PROCAUTIONS:

Thoroughly clean the spray tank, pumps, hoses, screens, nozzles, and any other equipment using water after each usage. Excessive discoloration may require the use of a tank cleaning solution. Prior to the application of any colorants, it may be necessary to change the ceramic seal in centrifugal pumps to a steel oil seal. There is no change needed for piston or diaphragm pumps. Seek guidance from your sales or technical representative for any suggestions regarding equipment.

WARNING:

Keep out of reach of children. Avoid contact with eyes or prolonged exposure to skin in accordance with safe industrial practices. Handle with care. Avoid unnecessary personal contact.

FIRST AID:

IN CASE OF EYE CONTACT: Flush eyes with running water for at least 15 minutes. If inflammation persists, consult a physician.

SKIN: Rinse with soap and water, and wash clothes before reuse.

Please note that this is intended for PROFESSIONAL use only. Refer to the MSDS for detailed information on health safety, risks, precautions, emergency first aid, protective equipment, and disposal.

NOTICE TO USER:

THIS PRODUCT IS SOLD WITHOUT WARRANTY AS TO HAZARD AND RESULTS

CAUTION: This product has the potential to stain a wide variety of surfaces, such as: Driveways, Cart Paths, Plants, Rocks, Stepping Stones, Sidewalks, and Pavers, To avoid inadvertent coloring, soak the area where color is not desired beforehand with clean water. and then rinse it thoroughly with water after each application. UNDILUTED PRODUCT SHOULD NOT BE APPLIED.

NET CONTENTS 2.5 GALLONS (320 FL OZ) ©2024 Regal Chemical, Inc.

RNV-RBST-01